

INRC-R. Rallying

Effective from - 5.9.2019

The Bulletin-No-2, will override point no 3 -(Addition only) in Bulletin- No 1, and is reproduced immediately below:

3- Addition – Ducting of cooling air to the intercooler is permitted from the bumper/front grill with a maximum outer diameter of 10 cm or two cooling ducts of 7 cm diameter or any other shape so long as the area is equal to, or less than those mentioned above. These ducts may be made of composite material. Water spray system may be adopted.

BULLETIN-2

Effective from - 5.9.2019

1. Article 7 of the INRC-R Technical Regulations-4W-2019

-Reads as-

7 - COOLING SYSTEM- A larger radiator may be fitted, the mounting points may be changed to accommodate the same, so long as it remains in the same location as the original radiator. Radiator screens are free. Cooling fans are free. The original water pump must be retained.

-Addition-The existing regulation follows below with the addition.

7 - COOLING SYSTEM- A larger radiator may be fitted, the mounting points may be changed to accommodate the same, so long as it remains in the same location as the original radiator. Radiator screens are free. Cooling fans are free. The original water pump must be retained.

The original Radiator Cowl may be modified to accommodate a larger radiator and the intercooler. Holes may be made (FREE SIZE AND SHAPE) in the front bumper/front bodywork/front grill, provided these are meant for the sole purpose of cooling the radiator/intercooler or brakes. However the minimum weight of the car should be respected.

Note:

Member of



Reads as- Means that this is the existing regulation

Addition - Means that this is in addition to the original wording/regulation



Member of

