



A-25 Krishna Towers
50 Sardar Patel Road, Chennai 600113
Ph : (91) (44) 22352673 / 22355304
E: admin@fmsci.in W: www.fmsci.co.in



BULLETIN	No.	02/2021
	Date	01 st July 2021
	Effective	Immediate
	No. of pages	One

2021 Two Wheeler Technical Regulations – Racing

CHAPTER 4: GROUP SPECIFIC REGULATIONS

4.1 SPECIFIC TECHNICAL REGULATIONS FOR STOCK (Group - D)

Art. 4.1.34 Fairing / Bodywork

Add the following new articles

- j) In case if the OE of the vehicle does not have a full lower fairing to catch the oil/fluid in case of engine breakdown; the lower fairing must be constructed to hold a minimum of 4 liters of Oil/Fluid. The lower edge of all the openings in the fairing must be positioned at least 70 mm above the bottom of the fairing. The upper edge of the transverse wall of the lower fairing must be at least 70 mm above the bottom. The angle between this wall and the floor must be $\leq 90^\circ$.
- k) Only in the case of modification as above, the lower fairing must incorporate a single opening of $\varnothing 25$ mm diameter in the front lower area. This hole must remain sealed. In case of wet race declared this hole should be unsealed to drain water out. Alternatively, a lower fairing without the $\varnothing 25$ mm opening may be used in the dry and replaced with one with the $\varnothing 25$ mm opening in case of a wet race being declared.



***** END *****